



STORAGE GUIDELINES

To ensure that your filter elements, including the well-known FormulaUFI types, perform optimally, and to guarantee their longevity, it is crucial to follow these storage guidelines:

RECOMMENDED STORAGE CONDITIONS

Packaging

- Store the products in their original, undamaged packaging as received.

Environment

- Keep the products in a clean, dry area to prevent moisture accumulation, which could lead to corrosion or mould growth.
- Avoid exposure to aggressive chemicals, solvents, or vapour that might damage the filter materials.

Protection from Light and Ozone:

- Shield the products from direct sunlight and ultraviolet (UV) light, which can degrade materials over time.
- Keep the products away from ozone sources, such as certain types of electrical equipment, to prevent premature aging of the rubber and plastic components.

Temperature and Humidity Control:

- Maintain an ambient temperature between 10°C and 40°C.
- Ensure that the relative humidity stays below 65% to avoid condensation and moisture absorption.

Positioning and Handling:

- Store filters in a stable position, avoiding pressure or mechanical deformation.

SHELF LIFE

- When stored as described above, UFI Filter Hydraulics elements should maintain their performance characteristics for up to 3 years from the date of manufacture.

ADDITIONAL NOTES

- Before use, we recommend that you visually inspect the filter elements to ensure they are free from damage or signs of deterioration.
- For critical applications, consider regular stock rotation to ensure that older products are used first.

If you need further information or any clarification, please feel free to contact our customer service team or your designated UFI representative.